



# CTO Carbon Block Cartridges

## Features and Specifications

- Proprietary Carbon Blend Formulations Used for Maximum Adsorption
- Cartridges will reduce Foul Odors, Chlorine Taste and Particulate Matter
- Polypropylene Outer Prefilter
- Consistent density for controlled flow rates and pressure loss
- Polypropylene or Colored Plastisol End Caps Available
- No GAC By-pass or Fluidizing
- All materials used in production are FDA Title 21 compliant
- Available up to 40" Lengths in 2.5" & 4.5" Outside Diameter
- Multiple Micron Ratings Available
- One Piece Carbon Block Construction Reduces Bypassing
- Extruded coconut carbon construction
- Plastisol end caps available for increased chemical and temperature resistance





# Specifications & Ordering

Media	
Micron Ratings	1, 3, 5, 10 micron
Construction	Carbon & Polypropylene
End Caps	Polypropylene
Operating Temperature	Cold or ambient water use only
Diameter	O.D. - 2.65" to 4.5" I.D. - 1.1" Center
Nominal Lengths	9.75" to 40"
Chlorine & Odor Reduction Capacity @ Flow	> 6,100 gal @ 1.0 GPM *
Initial Differential Pressure @ Flow	< 3 PSID @ 1 GPM *

\*Based on Manufacturer's Internal Testing

FDA compliance under Title 21 of the code of federal regulations for food contact applications

## Ordering Information

CB - 
 E - 
   - 
   - 
   - 
 S - 
   - 
  

Carbon Block	Media	Micron	Diameter	Length	Element Grade	End Cap	O-Ring
CB	E    Polypropylene	1 3 5 10	S = 2.5" Standard M = 4.5"	1 = 9.875 2 = 9.75 3 = 10 4 = 19.5 5 = 20 6 = 29.25 7 = 30 8 = 39 9 = 40 C = custom	S = Standard	1 = DOE-Plastisol 2 = 222/Fin 3 = 222/Spring 4 = 222/Flat 5 = 226/ Flat 6 = 226/Fin 7 = 226/Spring 8 = SOE/Spring 9 = DOE Gasket A = Custom	B = Buna V = Viton® T = Teflon® S = Silicone N = Neoprene D = EPDM